



The Clear Vision in Solar Protection®

PREMIUM LIFETIME WARRANTY

BENEFITS TO INSTALLATION

- Very aggressive adhesive eliminates fingering
- Great optical clarity with no distortion
- Unmatched scratch-resistant coating
- Static-free makes it plotter friendly

CARBONFX SERIES BLACK

COLOR-STABLE NR 2-PLY AUTOMOTIVE WINDOW FILMS

Series	VLT	10" Visor	20"	24"	36"	40"	60" x 100'
CARBONFX SERIES BLACK	5%, 15%, 20%, 30%, 35%, 43%, 50%						

A color-stable film with rich, black tone. The CarbonFX Series is a deep dyed 2-ply, 1.5 Mil polyester film in which UV inhibitors are utilized at multiple stages of the manufacturing process, ensuring the dyes will retain their color for years to come. This is the film of all films! Try it! Nothing else will compare. VLTs available: 5%, 15%, 20%, 30%, 35%, 43% and 50%.

Black NR Automotive Window Films	VLT	VLR	TSEt	TSEr	TSEa	UVR	TSEr	GR
CARBONFX 05	5	6	45	7	48	99	42	95
CARBONFX 15	16	6	46	6	48	99	41	82
CARBONFX 20	20	6	47	6	47	99	40	78
CARBONFX 30	32	6	53	6	41	99	36	65
CARBONFX 35	35	6	54	6	40	99	35	62
CARBONFX 43	43	6	56	6	38	99	33	53
CARBONFX 50	49	6	60	6	34	99	30	46

VLT = Visible Light Transmission
VLR = Visible Light Reflectance (Int)

TSEt = Total Solar Transmittance
TSEa = Total Solar Absorbance

TSEr = Total Solar Reflectance
UVR = Ultraviolet Rejected

GR = Glare Reduction
TSEr = Total Solar Energy Rejected

PREMIUM LIFETIME WARRANTY

BENEFITS TO INSTALLATION

- Very aggressive adhesive eliminates fingering
- Great optical clarity with no distortion
- Reliable unmatched scratch-resistant coating
- Static-free makes it plotter friendly

HYBRIDFX SERIES HIGH PERFORMANCE

COLOR-STABLE 2-PLY AUTOMOTIVE WINDOW FILMS



Series	VLT	20"	24"	36"	40"	60" x 100'
HYBRIDFX SERIES BLACK	5%, 20%, 40%, 45%, 50%					

A color-stable film that features a clean, neutral tone. The HybridFX Series is a hybrid metalized/deep dyed 2-ply, 1.5 Mil automotive film that offers great looks and excellent heat rejection. VLTs available: 5%, 20%, 40%, 45% and 50%.

High Performance Window Films	VLT	VLR	TSEt	TSEr	TSEa	UVR	TSEr	GR
HFX 05	4	5	21	12	68	99	61	94
HFX 20	20	6	32	9	59	99	51	78
HFX 40	41	7	45	7	48	99	41	57
HFX 45	45	7	48	7	44	99	39	52
HFX 50	50	7	54	7	39	99	36	40

VLT = Visible Light Transmission
VLR = Visible Light Reflectance

TSEt = Total Solar Transmittance
TSEa = Total Solar Absorbance

TSEr = Total Solar Reflectance
UVR = Ultraviolet Rejected

GR = Glare Reduction
TSEr = Total Solar Energy Rejected